

PVC Insulated Single Core

16mm² PVC Building Wire Green/Yellow 100m

Contact

Internal Sales
Phone: 1300 CABLES
olex.csquotes@nexans.com

Nexans Ref.: BAAP15A1001AAHN

Country Ref.: BAAP15A1001AAHN

EAN 13: 9319215008710

16mm² PVC Building Wire Green/Yellow

DESCRIPTION

Single Core Building Wires

- Single core,
- 0.6/1kV V-90 insulated,
- to AS/NZS 5000.1 (unsheathed),
- Copper conductors, 90°C.



STANDARDS

National AS/NZS 1125; AS/
NZS 5000.1



Conductor flexibility
Class 2



Rated Voltage Uo/U (Um)
0,6/1 kV



Cable flexibility
Rigid

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 29/6/24 www.nexans.com.au Page 1 / 3

PVC Insulated Single Core

16mm² PVC Building Wire Green/Yellow 100m

Contact

Internal Sales
Phone: 1300 CABLES
olex.csquotes@nexans.com

CHARACTERISTICS

Construction characteristics

Colour	Green / yellow
Conductor flexibility	Class 2
Conductor material	Copper
Conductor shape	Circular
Insulation	V-90
Type of conductor	Stranded copper
With Green/Yellow core	Yes

Dimensional characteristics

Approximate weight	17.0 kg/100m
Cable length	100 m
Conductor cross-section	16 mm ²
Neutral conductor section (when smaller)	- mm ²
Nominal insulation thickness	1.0 mm
Nominal overall diameter	6.9 mm
Number of cores	1

Electrical characteristics

Conductor AC resistance at 50 Hz	1.4 Ohm/km
Inductive reactance at 50Hz - flat touching	0.126 Ohm/km
Inductive reactance at 50Hz - trefoil	0.111 Ohm/km
Insulation resistance at 20°C	6 MOhm.km
Max. DC resistance of the conductor at 20°C	1.15 Ohm/km
Rated Voltage U ₀ /U (U _m)	0,6/1 kV

Mechanical characteristics

Cable flexibility	Rigid
Maximum Pulling Tension	1.1 kN

Usage characteristics

Minimum Bend Radius - During Installation (under Tension)	41 mm
Minimum Bend Radius - Installed	28 mm

PVC Insulated Single Core

















16mm² PVC Building Wire Green/Yellow 100m

Contact

Internal Sales
Phone: 1300 CABLES
olex.csquotes@nexans.com

















PVC INSULATED - CURRENT CARRYING CAPACITY TABLE SINGLE PHASE (IN AMPS)

Copper Conductor Insulation PVC Maximum Conductor Temperature 75C

Conductor cross-section [mm ²]	 Cu	 Cu	 Cu	 Cu	 Cu	 Cu	 Cu	 Cu
16	92	89	72	70	56	36	89	99
 Unenclosed spaced	 Unenclosed spaced from surface	 Unenclosed touching	 Enclosed conduit in air	 Thermal insulation, partially surrounded by thermal insulation	 Thermal insulation, completely surrounded by thermal insulation	 Underground ducts A - Underground Wiring Enclosure	 Underground ducts B - Individual Wiring Enclosure	

PVC INSULATED - CURRENT CARRYING CAPACITY TABLE THREE PHASE (IN AMPS)

Copper Conductor Insulation PVC Maximum Conductor Temperature 75C

Conductor cross-section [mm ²]	 Cu	 Cu	 Cu	 Cu	 Cu	 Cu	 Cu	 Cu
16	89	77	72	62	50	36	78	90
 Unenclosed spaced	 Unenclosed spaced from surface	 Unenclosed touching	 Enclosed conduit in air	 Thermal insulation, partially surrounded by thermal insulation	 Thermal insulation, completely surrounded by thermal insulation	 Underground ducts A - Underground Wiring Enclosure	 Underground ducts B - Individual Wiring Enclosure	