

# PVC Flat (TPS) 2 Core + Earth & 3 Core + Earth

## 2.5mm 2C&E Flat Black 100m

### Contact

Internal Sales  
Phone: 1300 CABLES  
olex.csquotes@nexans.com

**Nexans Ref.:** CNCP07A1002BKAA  
**Country Ref.:** CNCP07A1002BKAA  
**EAN 13:** 9322576240507

2X2.5mm<sup>2</sup> + E PVC Flat Red Black Cores with Black Sheath

### DESCRIPTION

- 2 & 3 core+earth flat,
- 450/750V V-90 insulated,
- 90°C PVC sheathed to AS/NZS 5000.2,
- Copper conductors.

Twin & Earth, Flats, TPS



### STANDARDS

**National AS/NZS 1125; AS/  
NZS 5000.2**



Conductor flexibility  
Class 2



Rated Voltage U<sub>o</sub>/U (U<sub>m</sub>)  
450/750 V



Cable flexibility  
Rigid



Bending factor when laying  
6 (xD)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 28/6/24 [www.nexans.com.au](http://www.nexans.com.au) Page 1 / 2

# PVC Flat (TPS) 2 Core + Earth & 3 Core + Earth

## 2.5mm 2C&E Flat Black 100m

Contact  
Internal Sales  
Phone: 1300 CABLES  
olex.csquotes@nexans.com

### CHARACTERISTICS

#### Construction characteristics

Colour	Black / black / red
Conductor flexibility	Class 2
Conductor material	Copper
Conductor shape	Circular
Insulation	V-90
Outer sheath	PVC
Type of conductor	Stranded copper
With Green/Yellow core	Yes
With smaller neutral conductor	No

#### Dimensional characteristics

Approximate weight	14.03 kg/100m
Cable length	100 m
Conductor cross-section	2.5 mm <sup>2</sup>
Earth conductor cross section	2.5 mm <sup>2</sup>
Neutral conductor section (when smaller)	- mm <sup>2</sup>
Nominal insulation thickness	0.7 mm
Nominal outer sheath thickness	1.0 mm
Nominal overall diameter	12.2 x 5.4
Number of cores	2
Number of earth cores	1

#### Electrical characteristics

Conductor AC resistance at 50 Hz	9.01 Ohm/km
Inductive reactance at 50Hz	0.159 Ohm/km
Insulation resistance at 20°C	12 MOhm.km
Max. DC resistance of the conductor at 20°C	7.41 Ohm/km
Rated Voltage U <sub>o</sub> /U (U <sub>m</sub> )	450/750 V

#### Mechanical characteristics

Cable flexibility	Rigid
-------------------	-------

#### Usage characteristics

Bending factor when installed	4 (xD)
Bending factor when laying	6 (xD)

### SELLING AND DELIVERY INFORMATION

Full pallet Quantity 8,000m 80 x 100m Spools

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 28/6/24 www.nexans.com.au Page 2 / 2

