

PVC SDI Single Core

2.5mm² PVC SDI Red Insulation White Sheath 100m

Contact
Internal Sales
Phone: 1300 CABLES
olex.csquotes@nexans.com

Nexans Ref.: AABP07A1001WTRD
Country Ref.: AABP07A1001WTRD
EAN 13: 9322576239952

2.5mm² PVC SDI Red Insulation White Sheath 100m

DESCRIPTION

Single Core PVC SDI Cable

- Single core, V-90 insulated,
- PVC sheathed to AS/NZS 5000,
- Copper conductors, 90°C.
- 1.0 to 16mm² 450/750V to AS/NZS 5000.2
- Larger sizes; 25 to 630mm² 0.6/1kV to AS/NZS 5000.1 are available on request



STANDARDS

National AS/NZS 1125; AS/
NZS 5000.1; AS/NZS 5000.2



Conductor flexibility
Class 2



Rated Voltage U_o/U_m (Um)
450/750 V



Cable flexibility
Rigid

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 28/6/24 www.nexans.com.au Page 1 / 3

The Nexans logo, featuring a stylized red 'N' followed by the word 'Nexans' in a black sans-serif font.

PVC SDI Single Core

2.5mm² PVC SDI Red Insulation White Sheath 100m

Contact
Internal Sales
Phone: 1300 CABLES
olex.csquotes@nexans.com

CHARACTERISTICS

Construction characteristics

Colour	White / red
Conductor flexibility	Class 2
Conductor material	Copper
Conductor shape	Circular
Insulation	V-90
Outer sheath	PVC
Type of conductor	Stranded copper

Dimensional characteristics

Approximate weight	4.8 kg/100m
Cable length	100 m
Conductor cross-section	2.5 mm ²
Nominal insulation thickness	0.7 mm
Nominal outer sheath thickness	0.8 mm
Nominal overall diameter	5.1 mm
Number of cores	1

Electrical characteristics

Conductor AC resistance at 50 Hz	9.01 Ohm/km
Inductive reactance at 50Hz - flat touching	0.159 Ohm/km
Inductive reactance at 50Hz - trefoil	0.143 Ohm/km
Insulation resistance at 20°C	9.2 MOhm.km
Max. DC resistance of the conductor at 20°C	7.41 Ohm/km
Rated Voltage U _o /U (U _m)	450/750 V

Mechanical characteristics

Cable flexibility	Rigid
Maximum installation tension	175 N

Usage characteristics

Minimum Bend Radius - During Installation (under Tension)	31 mm
Minimum Bend Radius - Installed	20 mm



















PVC SDI Single Core

2.5mm² PVC SDI Red Insulation White Sheath 100m

Contact
Internal Sales
Phone: 1300 CABLES
olex.csquotes@nexans.com



















PVC SDI - CURRENT CARRYING CAPACITY TABLE SINGLE PHASE (IN AMPS)

Copper Conductor Insulation PVC Maximum Conductor Temperature 75C

Conductor cross-section [mm ²]									
	Cu	Cu	Cu	Cu	Cu	Cu	Cu	Cu	Cu
2.5	30	29	23	24	20	12	43	32	36
 Unenclosed spaced	 Unenclosed spaced from surface	 Unenclosed touching							
 Enclosed conduit in air	 Thermal insulation, partially surrounded by thermal insulation		 Thermal Insulation, completely surrounded by thermal insulation						
 Buried direct	 Underground ducts A - Underground Wiring Enclosure			 Underground ducts B - Individual Wiring Enclosure					

PVC SDI - CURRENT CARRYING CAPACITY TABLE THREE PHASE (IN AMPS)

Copper Conductor Insulation PVC Maximum Conductor Temperature 75C

Conductor cross-section [mm ²]									
	Cu	Cu	Cu	Cu	Cu	Cu	Cu	Cu	Cu
2.5	29	25	23	21	17	12	37	27	33
 Unenclosed spaced	 Unenclosed spaced from surface	 Unenclosed touching							
 Enclosed conduit in air	 Thermal insulation, partially surrounded by thermal insulation		 Thermal Insulation, completely surrounded by thermal insulation						
 Buried direct	 Underground ducts A - Underground Wiring Enclosure			 Underground ducts B - Individual Wiring Enclosure					